














Models		Electric Mono 220 V-1,1 KWH	
Engines	Electric TRI 220/ 380 V-1,1 KWH gasoline Briggs\$ Stratton - 5CV	Dimensions (mm)	1090x 1426 x 1700
Vibration Frequency	4300 tr/ min	Weight with Mould	300 Kg
moulding Capacity		Daily production	
Length	400 mm.	Blocks of 10/20/40	2400
Width	1012 mm	Blocks of 15/20/40	1500
Width: Min./ Max.	190 mm / 200 mm	Blocks of 20/20/40	1200

Models	Types	Dimensions	p 100/40	Models	Types	Dimensions	p 100/40
	Full N° 14	5x20x40 10x20x40 15x20x40 20x20x40	19 10 6 5		Hollow N° 5	20x20x40	5*
	Full N° 14 JS	5x20x40 10x20x40 15x20x40 20x20x40	19 10 9 5		Hollow N° 14 JS	20x20x40	5***
	Hollow N° 84 N° 13 N° 13 B	8x20x40 10x20x40 12x20x40	12* 10* 8*		Line block N° 141 N° 142	15x20x40 20x20x40	6 5
	Hollow N° 13 JS N° 13B JS	10x20x40 12x20x40	10*** 8***		Hollow (beam) N° 112 N° 116 N° 120	12x20x52 16x20x52 20x20x52	3 4 4
	Hollow N° 91	15x20x40	6*		Hollow (fromwork) N° 212 N° 215 N° 220	12x20x50 15x20x50 20x20x50	6 4 4
	Hollow N° 90	15x20x40	6***				