



STAUNCH Pneumatic Waste Oil Extractor HC-2097

Features

1. Exclusive patented self-explosion-protection device
2. With a special handle bar to make the oil tray easy up and down
3. Be equipped with a transparent chamber to observe the waste oil before extract into tank.
4. Be equipped with a ball valve for the oil tray to inspect waste oil before entering the tank.

Technical Data

Model No.	HC-2097
Tank capacity(liter/US Gallon)	65/17.1
Air inlet Pressure(bar/psi)	6~8/87~116
Air inlet Connection(inch)	1/4"
Vacuum Degree(bar)	-1~0
Air Pressure for Oil Discharge(bar/psi)	0.7~1/10~15
Oil Temperature Range(°C)	40-60
Suction Speed @ Probe dia.φ8 & Oil 60OC (Liter/m/US Gallon/m)	6.5/1.72
Modular cylinder capacity(Liter/US Gallon)	9/2.4
Suction Hose (dia.@length)	φ19*1.5m
Draining Hose(dia.@length)	φ19*1.5m
Collection Bowl Capacity(liter/US Gallon)	20/5.3
Collection Bowl Diameter(mm)	400
Maximum Height(mm)	1890
Min Height (mm)	1670
Optional Extension Funnel Diameter(mm)	560
N.W./G.W.(kgs)	42/47
Dimension(mm)	550*445*1460

