



STAUNCH Submersible Sewage Pumps WQD7-10-0.75A

Application

Suitable for use with dirty water that is not chemically aggressive towards the material from which the pump is made. As a result of their reliability and the fact that they are easy to use, they are suitable for use in applications such as clearing dirty water, discharging domestic waste water, and for emptying collection traps containing particle up to a maximum of 35 mm.

Motor

1. Two-pole induction motor(n=2850 r.p.m)
2. Insulation Class B
3. Protection IP68
4. Continuous service S1
5. Thermal protector for single phase
6. Single-phase 220V/50Hz,60Hz if request
7. Three-phase 380V/50Hz, 60Hz if request



Operating conditions

1. 5m maximum immersion depth
2. Liquid temperature to 35 C
3. Maximum ambient temperature 40 C

No.	Model	OUTLET (Inch)	PARTICAL	BEARING	N.W (Kg)	LxWxH
D	WQD7-10-0.75A	2"	5	6201/6202	19	465x225x250

No.	MODEL	POWER		Q(m ⁵ /h)		0 1.8 3.6 5.4 7.2 9 10.8 12.6 14.4 16.2													
		kW	HP	Q(l/min)	0	30	60	90	120	150	180	210	240	270					
D	WQD7-10-0.75A	0.75	1	H	15	14	13	12	11	10									

